


## Tech Data

# Viega ProPress® 316 ECO Tubing Models 4008/4008XL



Nominal Tube Size inches	Part No.
½	82150
¾	82155
1	82160
1¼	82165
1½	82170
2	82175
2½	82180
3	82185
4	82190



This document is subject to updates. For the most current Viega technical literature please visit [www.viega.us](http://www.viega.us).



Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. **Installation by non-professionals may void Viega LLC's warranty.**

## Tube Dimensional Data

Nominal Tube Size inches	Outside Diameter (OD)		Inside Diameter (ID)		Wall Thickness		Weight	
	inches	mm	inches	mm	inches	mm	lb./ft.	per 20 ft. length
½	0.63	15.88	0.55	13.88	0.04	1.00	0.25	5.00
¾	0.88	22.23	0.78	19.83	0.05	1.20	0.43	8.60
1	1.13	28.58	1.03	26.18	0.05	1.20	0.55	11.00
1¼	1.38	35.00	1.26	32.00	0.06	1.50	0.85	17.00
1½	1.63	41.28	1.51	38.28	0.06	1.50	1.01	20.20
2	2.13	54.00	2.01	51.00	0.06	1.50	1.33	26.60
2½	2.63	66.68	2.47	62.68	0.08	2.00	2.18	43.60
3	3.13	79.38	2.97	75.38	0.08	2.00	2.60	52.00
4	4.13	104.78	3.97	100.78	0.08	2.00	3.46	69.20

Zero Lead identifies Viega products meeting the lead free requirements of NSF/ANSI/CAN 61 through testing under NSF/ANSI/CAN 372 (0.25% or less maximum weighted average lead content).

Pipe dimensionally (OD) conforms to ASME B88.

Conforms to ASTM A554 and ASTM A778.

Pipe wall conforms to the requirements of schedule 5S steel pipe per ASME B36.10M.

Wall thickness is the minimum allowable.



**Viega LLC**

585 Interlocken Blvd.  
Broomfield, CO 80021

Phone (800) 976-9819  
[www.viega.us](http://www.viega.us)

TD-PP 1122 ProPress 316 ECO Tubing

