Tech Data

Viega ProPress[®] Zero Lead Tailpiece P x F Union Model 2957ZL







Tailpiece

Water Meter

Diverting Valve

Description

The ProPress tailpiece is available in sizes $\frac{1}{2}$ x 1", $\frac{3}{4}$ x 1", 1" x 1" and 1" x 1¹/₄". ProPress tailpieces are used to connect piping to water meters, mixing valves, diverter valves and other plumbing and heating devices requiring a female BSP connection, commonly referred to as "straight threads".

The tailpiece nut for sizes $\frac{3}{4}$ " x 1" and 1" x 1¹/₄" is drilled for a seal wire, allowing for the installation of these sizes on $\frac{5}{4}$ ", $\frac{3}{4}$ " and 1" water meters. Seal wire size accommodated is AGW 18 or AGW 16.

Features

- ProPress end connection
- Female BSP half union
- EPDM sealing element
- Smart Connect[®] technology

Ratings

- Temperature Range: 0°F to 250°F
- Max. Operating Pressure: 300 psi



This document is subject to updates. For the most current Viega technical literature please visit <u>www.viega.us</u>.

0

Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. **Installation by**

non-professionals may void Viega LLC's warranty.




Zero lead identifies Viega products meeting the lead free requirements of NSF 61 through testing under NSF/ANSI 372 (0.25% or less maximum weighted average lead content.)

Approvals

- NSF/ANSI 61 and 372
- NSF-UP Code
- CSA

Component	Material	
Body	Zero Lead Bronze	
Sealing Element	EPDM	
Union Nut	Zero Lead Bronze	
Gasket	Peroxydical Cross-Linked EPDM	

Viega ProPress Tailpiece Zero Lead Bronze P x F BSP - Model 2957ZL



Part No.	Size (in) 1 2	A (in)	L (in)
79800	½ x 1 BSP	0.39	1.57
79805	34 x 1 BSP	0.63	1.87
79810	1 x 1 BSP	0.91	2.14
79815	1 x 1¼ BSP	0.73	2.04

Viega LLC 585 Interlocken Blvd. Broomfield, CO 80021

Phone (800) 976-9819 www.viega.us

