

## Tech Data

# Viega PureFlow® Crimp PolyAlloy Valves



### Description

Viega PureFlow PolyAlloy crimp valve and stop valves are available in crimp x crimp, crimp x lav connection, and crimp x closet connection. Approved for use with ASTM standard F876 PEX tubing.

### Features

- PolyAlloy polymer
- Crimp connection

### Ratings

- Temperature Range: 0°F - 180°F
- Max. Operating Pressure: 160 psi

### Approvals

- cNSF®us pw-372
  - NSF International Performance and Health Effects (Standards 14 and 61)
  - NSF certified to CSA B137.5 (Canadian Standards Association)
- NSF Certified to NSF-U.P. Code - approved for Uniform Plumbing Code, listed to ASTM F2159.
- ICC ES-PMG™ 1038 plumbing applications



This document is subject to updates. For the most current Viega technical literature please visit [www.viega.us](http://www.viega.us).




Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. **Installation by non-professionals may void Viega LLC's warranty.**




Zero lead identifies Viega products meeting the lead free requirements of NSF 61-G through testing under NSF/ANSI 372 (0.25% or less maximum weighted average lead content.)

Component	Material
Body	Polymer
Handle	Polymer
Connections	Polymer


### Viega PureFlow Crimp Valve Zero Lead PolyAlloy ¼ Turn - Model V5236



Part No.	Size (in)	L1 (in)	L2 (in)
	1		
43030	½	2.83	1.45
43040	¾	3.00	1.45

**Viega PureFlow Crimp Stop Valve Straight Zero Lead PolyAlloy Crimp x Lav ¼ Turn - Model V5036.30**

Part No.	Size (in) 1 2	L1 (in)	L2 (in)
43023	3/8 x 1/2 Lav	3.00	1.45

**Viega PureFlow Crimp Stop Valve Straight Zero Lead PolyAlloy Crimp x Closet ¼ Turn - Model V5036.31**

Part No.	Size (in) 1 2	L1 (in)	L2 (in)
43002	3/8 x 1/2 Closet	3.00	1.45
43003	1/2 x 1/2 Closet	3.00	1.45