# **Tech Data**

# Viega PureFlow® Press Commercial Ball Valve, Model 2870ZL



## **Description**

The Viega PureFlow Press commercial ball valve available in sizes from ½" to 2" is equipped with a zero lead bronze body, stainless steel ball and EPDM seals.

## **Features**

- Stainless steel ball
- PTFE seat
- Brass stem

#### **Accessories**

- Handle, Model 2971.8
- T-Handle, Model 2971.26
- Insulated Handle, Model 2971.46
- Stem Extension, Model 2971.66

## **Ratings**

Temperature Range: 0°F - 180°FMax. Operating Pressure: 160 psi


### **Approvals**

- NSF<sub>®</sub>-61-372
- NSF<sub>®</sub>-U.P. Code
- ASME112.4.14/CSA B125.14
- IAPMO/ANSI Z1157
- ASTM F877/F3253/F3347
- NSF/ANSI 359




This document is subject to updates. For the most current Viega technical literature, please visit <u>www.viega.us</u>.

Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. **Installation by non-professionals may void Viega LLC's warranty.** 



Component	Material				
Body	Zero Lead Bronze CC246E				
Ball	Stainless Steel				
Seat	PTFE Brass				
Stem					
Stem Seals	EPDM				
Nut	Zinc-Plated Steel				

## Viega PureFlow Press Ball Valve Zero Lead Brass P x P - Model 2870ZL\*



Part No.	Size (in)	H1 (in)	H2 (in)	L1 (in)	L2 (in)	L3 (in)	A1 (in)	A2 (in)	Cv (US gal/min)
87900	1/2	2.01	0.59	1.58	1.30	4.57	1.06	0.79	4.96
87905	3/4	2.01	0.63	1.58	1.30	4.57	1.06	0.83	13.5
98200	1	2.01	0.63	1.58	1.58	4.57	1.02	0.87	15.1
98201	11/4	2.09	0.79	1.89	1.73	4.57	1.02	0.95	32.7
98202	11/2	2.48	1.10	2.01	1.89	5.79	1.14	1.02	54.7
98203	2	2.68	1.18	2.28	2.28	5.79	1.22	1.22	88.2



Phone (800) 976-9819 www.viega.us

