## **Tech Data**

# Viega ProPress® 316 3-Piece Ball Valve Model 4370.8



### **Description**

The ProPress 316 3-piece ball valve is equipped with a full port, 316 stainless steel 3-piece body. The ball valve features FKM

sealing elements, PTFE stem seals, lockable metal handle and Viega's Smart Connect® technology for easy identification of unpressed connections during pressure testing.

#### **Features**

- 316 stainless steel ball
- Blowout-proof 316 stainless steel stem
- 304 stainless steel locking handle
- Adjustable packing nut
- Reinforced PTFE seats
- Smart Connect technology
- ISO 5211 mounting pad



This document is subject to updates. For the most current Viega technical literature please visit www.viega.us.

Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. Installation by non-professionals may void Viega LLC's warranty.

## **Ratings**


- 250 CWP
- Max. operating pressure: 200 psiTemperature range: 14°F to 250°F

## **Approvals**

■ Conforms to MSS SP-110

Valve Size	Valve Body Bolt & Nut Size		Bolt Torque +/- 5		Valve Stem Nu Stem Nu Stem Nu		n Nut
(in)			ft/lbs	(Nm)	(mm)	(ft/lbs)	(Nm)
1/2	M8 x 45	M8	7.5	(10)	AF 16	7.5	10
3/4	M8 x 56	M8	7.5	(10)	AF 18	7.5	10
1	M8 x 65	M8	15	(20)	AF 21	11	15
11⁄4	M10 x 75	M10	15	(20)	AF 22	11	15
1½	M10 x 90	M10	22.5	(30)	AF 24	18.5	25
2	M10 x 100	M10	22.5	(30)	AF 24	18.5	25

# Viega ProPress 316 3-Piece Ball Valve Stainless Steel P x P - Model 4370.8



Part No.	Size (in)	B (in)	C (in)	D (in)
S/S 316	1			
85132	1/2	5.41	3.99	2.28
85133	3/4	5.79	5.88	2.85
85134	1	6.00	5.88	2.93
85136	11/4	6.61	7.54	3.27
85137	1½	7.26	7.54	3.57
85138	2	9.67	7.54	3.89



Phone (800) 976-9819 www.viega.us

