



VIZM7.EX6157 Fittings, Rubber Gasketed Certified for Canada

[Page Bottom](#)

Fittings, Rubber Gasketed Certified for Canada

[See General Information for Fittings, Rubber Gasketed Certified for Canada](#)

VIEGA L L C

EX6157

MOUNTAIN VIEW CORPORATE CENTER
BLDG 1, SUITE 395
12303 AIRPORT WAY
BROOMFIELD, CO 80021 USA

Press fitting

MegaPress rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with Schedule 10 and Schedule 40 steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Type	Size (in.)	Rated Pressure (kPa)
Cap (P)	1-1/4, 1-1/2, 2	1210
Coupling (P x P)	1-1/4, 1-1/2, 2	1210
90 Degree elbow (P x P)	1-1/4, 1-1/2, 2	1210
45 Degree elbow (P x P)	1-1/4, 1-1/2, 2	1210
Tee (P x P x P)	1-1/4, 1-1/2, 2	1210
Reducing tee (P x P x P)	1-1/2 x 1-1/2 x 1-1/4; 2 x 2 x 1-1/4, 1-1/2	1210
Reducing tee (P x P x NPT)	1 x 1 x 1/2, 3/4; 1-1/2 x 1-1/2 x 1/2, 3/4, 1, 1-1/4; 2 x 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2	1210
Union (P x P)	1-1/4, 2	1210
Flange adapter (P x F)	1-1/4, 1-1/2, 2	1210
Male adapter (P x MNPT)	1, 1-1/4, 1-1/2, 2	1210
Female adapter (P x FNPT)	1 x 1/2, 3/4, 1; 1-1/4 x 1/2, 3/4, 1, 1-1/4; 1-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210

MegaPress rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with Schedule 40 steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Type	Size (in.)	Rated Pressure (kPa)
Cap (P)	1	1210
Coupling (P x P)	1	1210
90 Degree elbow (P x P)	1	1210
45 Degree elbow (P x P)	1	1210
Tee (P x P x P)	1	1210
Reducing tee (P x P x P)	1-1/2 x 1-1/2 x 1; 2 x 2 x 1	1210
Union (P x P)	1	1210
Flange adapter (P x F)	1	1210

All model MegaPress rubber gasketed fittings are suitable for use in dry pipe systems for temperatures to -40 degree F.

ProPress 304 stainless rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with listed Viega Eco-pipe and 304 stainless steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Type	Size (in.)	Rated Pressure (kPa)
Adapter (P x MNPT)	1/2 x 1/2, 3/4; 3/4 x 1/2, 3/4, 1; 1 x 3/4, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/2; 2 x 2	1210
Adapter (P x FNPT)	1/2 x 1/2; 3/4 x 1/2, 3/4; 1 x 1/2, 3/4, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/4, 1-1/2; 2 x 1, 1-1/2, 2	1210
Cap	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
Coupling (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
Slip coupling (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
Flange adapter (P x F)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
90 Degree elbow (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
90 Degree elbow (PE x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
45 Degree elbow (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
45 Degree elbow (PE x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
Tee (P x P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	1210
Reducing tee (P x P x P)	3/4 x 3/4 x 1/2; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1-1/2 x 1/2, 3/4, 1; 2 x 2 x 1/2, 3/4, 1, 1-1/2	1210
Reducing tee (P x P x FNPT)	3/4 x 3/4 x 1/2, 3/4; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1-1/2 x 1/2, 3/4, 1; 2 x 2 x 1/2, 3/4, 1	1210
Reducer (PE x P)	3/4 x 1/2; 1 x 1/2, 3/4; 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1/2, 3/4, 1; 2 x 1/2, 3/4, 1; 1-1/2	1210
Union (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210

ProPress 316 rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with Viega Eco pipe and Viega 304 stainless steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Type	Size (in.)	Rated Pressure (psig)
Adapter (P x MNPT)	1/2 x 1/2, 3/4; 3/4 x 1/2, 3/4, 1; 1 x 3/4, 1; 1-1/4 x 1-1/4;	1210

	1-1/2 x 1-1/2; 2 x 2	
Adapter (P x FNPT)	1/2 x 1/2; 3/4 x 1/2, 3/4; 1 x 1/a2, 3/4, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/4, 1-1/2; 2 x 1, 1-1/2, 2	1210
Cap	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
Coupling (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
Slip Coupling (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
Flange Adapter (P x F)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
90 Degree Elbow (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
90 Degree Elbow (PE x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
45 Degree Elbow (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
45 Degree Elbow (PE x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
Tee (P x P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210
Reducing Tee (P x P x P)	3/4 x 3/4 x 1/2; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1-1/2 x 1/2, 3/4, 1; 2 x 2 x 1/2, 3/4, 1, 1-1/2	1210
Reducing Tee (P x P x FNPT)	3/4 x 3/4 x 1/2, 3/4; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1-1/2 x 1/2, 3/4, 1; 2 x 2 x 1/2, 3/4, 1	1210
Reducer (PE x P)	3/4 x 1/2; 1 x 1/2, 3/4; 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1/2, 3/4, 1; 2 x 1/2, 3/4, 1, 1-1/2	1210
Union (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	1210

P - Press

F - Flange

FNPT - Female NPT Threads

MNPT - Male NPT Threads

10 refers to Schedule 10 steel sprinkler pipe in accordance with NFPA 13.

40 refers to Schedule 40 steel sprinkler pipe in accordance with NFPA 13.

Press fitting

Model ProPress rubber gasketed fittings constructed from Red Brass in the following types, sizes and rated pressures are intended for use with copper tube, Type K, L and M and are to be installed in accordance with the manufacturer's installation instructions and a Listed Model CT-400 Class II crimping tool manufactured by Ridge Tool under File E225870.

Type	Size, in.	Rated Pressure (kPa)
Cap	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
Coupling	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210

Reducing coupling	3/4 x 1/2; 1 x 1/2, 3/4; 1-1/4 x 3/4, 1; 1-1/2 x 3/4, 1, 1-1/4; 2 x 3/4, 1, 1-1/4, 1-1/2	1210
90° Elbow	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
90° Elbow NPT	3/4 x 1/2, 3/4; 1 x 1/2, 1; 1-1/4 x 1/2; 1-1/2 x 1-1/2; 2 x 2	1210
90° Elbow weld	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
90° Elbow flange	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
45° Elbow	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
45° Elbow NPT	3/4 x 3/4; 1 x 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/2; 2 x 2	1210
45° Elbow weld	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
45° Elbow flange	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
Reducer	1 x 3/4; 1-1/4 x 1-1/4; 1-1/2 x 1-1/4; 2 x 1-1/2	1210
Reducer flange	1-1/4 x 1; 1-1/2 x 1, 1-1/4; 2 x 1, 1-1/4, 1-1/2; 2-1/2 x 2; 3 x 2, 2-1/2; 4 x 2, 2-1/2, 3	1210
Tee	3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	1210
Reducing tee	1/2 x 1/2 x 1; 1 x 1/2, 3/4 x 1; 1 x 1 x 1/2, 3/4, 1-1/4; 1-1/4 x 1/2 x 1-1/4; 1-1/4 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1/2 x 1-1/2; 1-1/2 x 1 x 1, 1-1/2; 1-1/2 x 1-1/4 x 1, 1-1/4; 1-1/2 x 1-1/2 x 1/2, 3/4, 1, 1-1/4; 2 x 1/2 x 2; 2 x 1 x 1, 2; 2 x 1-1/4 x 1-1/4; 2 x 1-1/2 x 1, 1-1/4, 1-1/2, 2; 2 x 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2 x 1-1/2 x 1/2, 3/4; 2-1/2 x 2 x 2-1/2; 3 x 2, 2-1/2 x 3; 3 x 3 x 1-1/2, 2, 2-1/2; 4 x 4 x 1-1/2, 2, 2-1/2, 3; 4 x 2, 2-1/2 x 4	1210
Reducing tee NPT	1 x 1 x 1/2; 1-1/4 x 1-1/4 x 1/2; 1-1/2 x 1-1/2 x 1/2; 2 x 2 x 1/2; 2-1/2 x 3/4, 2 x 2-1/2; 3 x 3/4, 2 x 3; 3 x 3 x 3/4; 4 x 3/4 x 4; 4 x 2 x 4; 4 x 4 x 3/4, 2	1210
Union	1, 1-1/4, 1-1/2, 2	1210
Union NPT	1, 1-1/4, 1-1/2, 2	1210
Adapter NPT	1 x 1/2, 3/4, 1, 1-1/4; 1-1/4 x 1/2, 1, 1-1/4, 1-1/2;	1210

	1-1/2 x 1-1/4, 1-1/2, 2; 2 x 1-1/2, 2, 2-1/2; 3 x 3; 4 x 4	
Adapter weld	1/2 x 1, 1-1/4, 1-1/2, 2; 1 x 1-1/4, 1-1/2, 2; 1-1/4 x 1-1/2, 2; 1-1/2 x 2; 2 x 3, 4; 2-1/2 x 2, 3, 4	1210
Adapter flange	1, 1-1/2, 1-1/2, 2, 2-1/2, 3, 4	1210
Adapter weld x NPT	1 x 1/2, 1; 1-1/4 x 1/2, 1-1/4; 1-1/2 x 1-1/2; 2 x 2	1210
Adapter NPT x NPT	1 x 1-1/4, 1-1/2; 1-1/4 x 1-1/2; 1-1/2 x 2	1210
Adapter flange x NPT	1, 1-1/4, 1-1/2, 2	1210

All model ProPress rubber gasketed fittings are suitable for use in dry pipe systems for temperatures to -40 degree C.

Press fitting

Zero Lead ProPress rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with copper tube, Type K, L and M and are to be installed with a RIDGID Tool Company Electro-Hydraulic Press Tool in accordance with the manufacturer's installation instructions.

Model	Type	Size (in.)	Rated Pressure (kPa)
2925.5ZL	90° Elbow drop w/wall plate, P x F NPT	3/4 x 3/4	1210
2917.2ZL	Tee P x P x F NPT	3/4 x 3/4 x 1/2, 3/4; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4; 1-1/2 x 1-1/2 x 1/2, 3/4; 2 x 2 x 1/2, 3/4	1210
2911ZL	Male adapter P x M NPT	3/4 x 1/2, 3/4, 1; 1 x 3/4, 1, 1-1/4; 1-1/4 x 1, 1-1/4; 1-1/2 x 1-1/4, 1-1/2, 2; 2 x 1-1/2, 2	1210
2912ZL	Female adapter P x F NPT	3/4 x 1/2, 3/4; 1 x 1/2, 3/4, 1, 1-1/4; 1-1/4 x 1/2, 1, 1-1/4, 1-1/2; 1-1/2 x 1-1/4, 1-1/2; 2 x 2	1210
2967ZL	Di-electric union, P x F NPT	3/4, 1, 1-1/4, 1-1/2, 2	1210
2914.2ZL	90° Elbow P x FNPT	3/4 x 1/2, 3/4; 1 x 1/2, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/2; 2 x 2	1210
2960ZL	Union P x P	3/4, 1, 1-1/4, 1-1/2, 2	1210
2962ZL	Union P x FNPT	3/4, 1, 1-1/4, 1-1/2, 2	1210
2965ZL	Union P x MNPT	3/4, 1, 1-1/4, 1-1/2, 2	1210
2959.5ZL	Adapter flange P x Flange	1, 1-1/4, 1-1/2, 2	1210
2915.1ZL	Reducer FTG x P	1-1/2 x 1/2; 2 x 1/2, 3/4	1210

All model ProPress rubber gasketed fittings are suitable for use in dry pipe systems for temperatures to -40 degree C.

P - Press

F NPT - Female National Pipe Thread

M NPT - Male National Pipe Thread

FTG - Copper tube end (fitting)

Last Updated on 2016-12-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".