

Tech Data

Viega ProPress® Valves and Accessories by Model

Zero Lead Bronze Ball Valve - P x P - Model 2971.1ZL



- Smart Connect technology
- 250 CWP
- Body: Two Piece Zero Lead Bronze
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters:
250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

Part No.	Size (in)
79920	1/2
79925	3/4
79930	1
79935	1 1/4

Zero Lead Bronze Ball Valve - P x P - Model 2971.3ZL



- Smart Connect technology
- 250 CWP
- Body: Two Piece Zero Lead Bronze
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof 316 Stainless Steel
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters:
250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

Part No.	Size (in)
79923	1/2
79928	3/4
79933	1
79938	1 1/4

Zero Lead Bronze Ball Valve - P x P - Model 2970.1ZL



- Smart Connect technology
- 250 CWP
- Body: Two Piece Zero Lead Bronze
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters:
250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

Part No.	Size (in)
79115	1 1/2
79120	2

Zero Lead Bronze Ball Valve - P x P - Model 2970.3ZL



- Smart Connect technology
- 250 CWP
- Body: Two Piece Zero Lead Bronze
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof 316 Stainless Steel
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters:
250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

Part No.	Size (in)
79840	1 1/2
79845	2

Zero Lead Bronze Ball Valve - P x FPT - Model 2971.4ZL



- Smart Connect technology
- 250 CWP
- Body: Two Piece Zero Lead Bronze
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters:
250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

Part No.	Size (in)
79970	1/2
79975	3/4
79980	1

Zero Lead Bronze Ball Valve - P x Hose - Model 2971.6ZL



- Smart Connect technology
- 250 CWP
- Body: Two Piece Zero Lead Bronze
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: NSF-61-372, U.P. Code, ASME A112.4.14
- Conforms to: MSS SP-110
- Parameters:
250 psi Maximum Working Pressure
0° - 250°F Operating Temperature

Part No.	Size (in)
79875	1/2
79876	3/4

Bronze Ball Valve - P x P - Model 2973



- Smart Connect technology
- 200 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO IGC 157
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure 0° - 250°F Operating Temperature



Part No.	Size (in)
24000	1/2
24005	3/4
24010	1
24015	1 1/4
24020	1 1/2
24025	2

Bronze Ball Valve - P x FPT - Model 2973.1



- Smart Connect technology
- 200 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO IGC 157
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure 0° - 250°F Operating Temperature



Part No.	Size (in)
24030	1/2
24035	3/4
24040	1

Bronze Ball Valve - P x Hose - Model 2973.2



- Smart Connect technology
- 200 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO IGC 157
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure 0° - 250°F Operating Temperature



Part No.	Size (in)
24090	1/2
24095	3/4

Bronze Gas Ball Valve - P x P - Model 0670



- Smart Connect technology
- 600 WOG
- Body: Two Piece Bronze Body
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: HNBR
- Listings: CSA LC4
- Conforms to: IFGC NFPA 54
- Parameters: 125 psi Maximum Working Pressure -40° - 180°F Operating Temperature

Part No.	Size (in)
19648	1/2
19653	3/4
19658	1
19663	1 1/4
19668	1 1/2
19673	2

316 Stainless Steel Ball Valve - P x P - Model 4070



- Smart Connect technology
- Body: 316 Stainless Steel
- Ball: 316 Stainless Steel Fullport
- Stem: Blow-out Proof 316 Stainless Steel
- Sealing Element: EPDM
- Listings: NSF-61-372
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure 0° - 250°F Operating Temperature

Part No.	Size (in)
81080	1/2
81085	3/4
81090	1
81095	1 1/4
81100	1 1/2
81105	2

316 Stainless Steel Three Piece Ball Valve - P x P - Model 4370.8



- Smart Connect technology
- Body: Three Piece 316 Stainless Steel
- Ball: 316 Stainless Steel Fullport
- Stem: Blow-out Proof 316 Stainless Steel
- Sealing Element: FKM
- Conforms to: MSS SP-110
- Parameters: 200 psi Maximum Working Pressure 0° - 250° Operating Temperature

Part No.	Size (in)
85132	1/2
85133	3/4
85134	1
85136	1 1/4
85137	1 1/2
85138	2

Inline Check Valve - Model 2974ZL



- Smart Connect technology
- Body: Zero Lead Bronze
- Check Valve Insert: POM Bubble Tight
- Cracking Pressure: 0.5 PSIG
- Sealing Element: EPDM
- Listings: UPC NSF-61-372
- Parameters:
200 psi Maximum Working Pressure
0° - 180°F Operating Temperature

Part No.	Size (in)
79035	1/2
79040	3/4
79045	1
79050	1 1/4
79055	1 1/2
79060	2

Semi Lug Butterfly Valve - Model 2873.81



- Body: Semi-Lug Spheroidal Cast Iron
- Disc: 316 Stainless Steel
- Stem: 316 Stainless Steel
- Handle: 10 Position Spring Locking Handle
- Mounting Flange: ISO 5211
- Liner: EPDM
- Conforms to: MSS SP 67, AWWA C504-6
- Parameters:
250 psi Maximum Working Pressure
0° - 200°F Operating Temperature

Part No.	Size (in)
22074	2 1/2
22075	3
22076	4

Ball Valve Lockable Metal Handle - Model 2971.8

*Use with Models 2971ZL



Part No.	Size (in)
22170	1/2 & 3/4
22172	1 & 1 1/4

Ball Valve Stem Extension Kit - Model 2971.96

*Use with Models 2971ZL



Part No.	Size (in)
23443	1/2 & 3/4
23445	1 & 1 1/4

Ball Valve Metal Handle - Model 2973.8

*Use with Models 2973



Part No.	Size (in)
22176	1/2
22178	3/4 & 1
22180	1 1/4 & 2

Ball Valve Stem Extension Kit - Model 2973.96

*Use with Models 2973



Part No.	Size (in)
23449	1/2
23451	3/4 & 1
23453	1 1/4 to 2

Ball Valve Lockable Metal Handle - Model 2970.8

*Use with Model 4070 and 2970ZL



Part No.	Size (in)
22143	1/2, 3/4, 1
22163	1 1/4, 1 1/2, 2

Ball Valve Stem Extension Kit - Model 2970.96

*Use with Model 4070 and 2970ZL



Part No.	Size (in)
23442	1/2, 3/4, 1
23444	1 1/4, 1 1/2, 2

Flange Bolt Set - Model 2959.7

*Use with Model 2873.81



Part No.	Size (in)
19748	1, 1 1/4, 1 1/2
19758	2, 2 1/2, 3
19763	4

Viega LLC
585 Interlocken Blvd.
Broomfield, CO 80021

Phone (800) 976 9819
www.viega.us

TD-PP 1218 Valves and Accessories by Model

