

## VIZM.EX6157 - Fittings, Rubber Gasketed

## Fittings, Rubber Gasketed

See General Information for Fittings, Rubber Gasketed

**VIEGA L L C**

EX6157

585 Interlocken Blvd  
Broomfield, CO 80021 USA

**Press fitting**

MegaPress rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with Schedule 10 and Schedule 40 steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Model	Type	Size (in.)	Rated Pressure (psig)
4856	Cap (P)	1-1/4, 1-1/2, 2	175
4856	Cap (P)	2-1/2, 3, 4	175
4815	Coupling (P x P)	1-1/4, 1-1/2, 2	175
4815	Coupling w/ stop (P X P)	2-1/2, 3, 4	175
4815.5	Extended Coupling w/ No stop (PxP)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4815.5	Coupling w/ No stop	2-1/2, 3, 4	175
4816	90 Degree Elbow (P x P)	1-1/4, 1-1/2, 2	175
4816	90 Degree Elbow (P x P)	2-1/2, 3, 4	175
4816.1	90 Degree Street Elbow (P x FTG)	2-1/2, 3, 4	175
4826	45 Degree elbow (P x P)	1-1/4, 1-1/2, 2	175
4826	45 Degree Elbow (P X P)	2-1/2, 3, 4	175
4826.1	45 Degree Street Elbow (P X FTG)	2-1/2, 3, 4	175
4818	Tee (P x P x P)	1-1/4, 1-1/2, 2	175
4818	Tee (P X P X P)	2-1/2, 3, 4	175
4815.2	Reducer (P x P)	3/4x1/2; 1x1/2, 3/4; 1-1/4x3/4, 1; 1-1/2x1-1/4; 2x1-1/4, 1-1/2	175
4815.1	Reducer (FTG X P)	2-1/2 X 1, 1-1/4, 1-1/2, 2; 3 X 1-1/4, 1-1/2, 2, 2-1/2; 4 X 1-1/2, 2, 2-1/2, 3	175
4818	Reducing tee (P x P x P)	1-1/2 x 1-1/2 x 1-1/4; 2 x 2 x 1-1/4, 1-1/2; 1-1/4 x 1-1/4 x 1/2, 3/4	175

4818	Reducing Tee (P X P X P)	2-1/2 X 2-1/2 X 1-1/2, 2; 3 X 3 X 1-1/4, 1-1/2, 2, 2-1/2; 4 X 4 X 1-1/2, 2, 2-1/2, 3	175
4817.2	Reducing tee (P x P x NPT)	1 x 1 x 1/2, 3/4; 1-1/2 x 1-1/2 x 1/2, 3/4, 1, 1-1/4; 2 x 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2	175
4817.2	Female Reducing Tee (P x P x FNPT)	1-1/4x1-1/4x3/4, 1	175
4817.2	Female Reducing Tee (P x P x FNPT)	2-1/2 X 2-1/2 X 3/4; 3 X 3 X 3/4; 4 X 4 X 3/4	175
4860	Union (P x P)	1-1/4, 2	175
4859.5	Flange adapter (P x F)	1-1/4, 1-1/2, 2	175
4811	Male adapter (P x MNPT)	1, 1-1/4, 1-1/2, 2	175
4811	Adapter (P X MNPT)	2-1/2, 3, 4	175
4812	Female adapter (P x FNPT)	1 x 1/2, 3/4, 1; 1-1/4 x 1/2, 3/4, 1, 1-1/4; 1-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4812	Female Adapter (P X FNPT)	2-1/2, 3, 4	175

MegaPress rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with Schedule 40 steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Model	Type	Size (in.)	Rated Pressure (psig)
4856	Cap (P)	1	175
4815	Coupling (P x P)	1	175
4816	90 Degree elbow (P x P)	1	175
4826	45 Degree elbow (P x P)	1	175
4818	Tee (P x P x P)	1	175
4818	Reducing tee (P x P x P)	1-1/2 x 1-1/2 x 1; 2 x 2 x 1	175
4860	Union (P x P)	1	175
4859.5	Flange adapter (P x F)	1	175

MegaPress rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with Schedule 10 and Schedule 40 steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Model	Outlet Type	Pipe	Size, in	Rated Pressure, psi
42122	Threaded	10	1-1/2 X 3/4	175
42122	Threaded	10	2 X 3/4	175
42122	Threaded	10	2-1/2 X 3/4	175

42122	Threaded	10	3 X 3/4	175
42122	Threaded	10	4 X 3/4	175
42122	Threaded	10	6 X 3/4	175

All model MegaPress rubber gasketed fittings are suitable for use in dry pipe systems for temperatures to -40 degree F.

P - Press

F - Flange

FTG - Plain End Fitting

FNPT - Female NPT Threads

MNPT - Male NPT Threads

10 refers to Schedule 10 steel sprinkler pipe in accordance with NFPA 13.

40 refers to Schedule 40 steel sprinkler pipe in accordance with NFPA 13.

MegaPress rubber gasketed fittings constructed from 304 stainless steel in the following types, sizes and rated pressures are intended for use with the pipe types listed below and are to be installed in accordance with the manufacturer's installation instructions.

Model	Type	Pipe	Size (in.)	Rated Pressure (psig)
4111	Adapter (P X MNPT)	10S, 40S	1/2 X 1/2; 3/4 X 1/2, 3/4 X 3/4; 1 X 1; 1-1/2 X 1-1/2; 2 X 2	175
4112	Adapter (P X FNPT)	10S, 40S	1/2 X 1/2; 3/4 X 3/4; 1 X 1; 1-1/2 X 1-1/2; 2 X 2	175
4115	Coupling w/ Stop (P X P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
4115.1	Reducer (FTG X P)	10S, 40S	3/4 x 1/2; 1 x 1/2, 1 X 3/4; 1-1/2 X 3/4, 1-1/2 x 1; 2 x 1, 2 x 1-1/2	175
4115.2	Reducer (P X P)	10S, 40S	3/4 x 1/2; 1 x 3/4; 1-1/2 x 1; 2 x 1-1/2	175
4115.5	Coupling w/ no stop (P X P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
4116	90 Degree elbow (P x P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
4116.1	90 Degree elbow (FTG x P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175

4117.2	Tee (P X P X FNPT)	10S, 40S	3/4 X 3/4 X 1/2, 3/4; 1 X 1 X 1/2, 3/4; 1-1/2 X 1-1/2 x 1/2, 3/4, 1; 2 X 2 X 1/2, 3/4, 1	175
4118	Tee (P X P X P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
4118	Reducing Tee (P X P X P)	10S, 40S	3/4 x 3/4 x 1/2; 1 x 1 x 1/2, 3/4; 1-1/2 X 1-1/2 x 1/2, 3/4, 1; 2 X 2 X 1/2, 3/4, 1, 1-1/2	175
4126	45 Degree elbow (P x P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
4126.1	45 Degree elbow (FTG X P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
4156	Cap (P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
4159	Flange (P X F)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175

MegaPress rubber gasketed fittings constructed from 316 stainless steel in the following types, sizes and rated pressures are intended for use with the pipe types listed below and are to be installed in accordance with the manufacturer's installation instructions.

Model	Type	Pipe	Size (in.)	Rated Pressure (psig)
5111	Adapter (P X MNPT)	10S, 40S	1/2 X 1/2; 3/4 X 1/2, 3/4 X 3/4; 1 X 1; 1-1/2 X 1-1/2; 2 X 2	175
5112	Adapter (P X FNPT)	10S, 40S	1/2 X 1/2; 3/4 X 3/4; 1 X 1; 1-1/2 X 1-1/2; 2 X 2	175
5115	Coupling w/ Stop (P X P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
5115.1	Reducer (FTG X P)	10S, 40S	3/4 x 1/2; 1 x 1/2, 1 X 3/4; 1-1/2 X 3/4, 1-1/2 x 1; 2 x 1, 2 x 1-1/2	175
5115.2	Reducer (P X P)	10S, 40S	3/4 x 1/2; 1 x 3/4; 1-1/2 x 1; 2 x 1-1/2	175
5115.5	Coupling w/ no stop (P X P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
5116	90 Degree elbow (P x P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175

5116.1	90 Degree elbow (FTG x P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
5117.2	Tee (P X P X FNPT)	10S, 40S	3/4 X 3/4 X 1/2, 3/4; 1 X 1 X 1/2, 3/4; 1-1/2 X 1-1/2 x 1/2, 3/4, 1; 2 X 2 X 1/2, 3/4, 1	175
5118	Tee (P X P X P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
5118	Reducing Tee (P X P X P)	10S, 40S	3/4 x 3/4 x 1/2; 1 x 1 x 1/2, 3/4; 1-1/2 X 1-1/2 x 1/2, 3/4, 1; 2 X 2 X 1/2, 3/4, 1, 1-1/2	175
5126	45 Degree elbow (P x P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
5126.1	45 Degree elbow (FTG X P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
5156	Cap (P)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175
5159	Flange (P X F)	10S, 40S	1/2, 3/4, 1, 1-1/2, 2	175

10S refers to stainless steel schedule 10 pipe constructed in accordance with ASTM A312. 40S refers to stainless steel schedule 40 pipe constructed in accordance with ASTM A312.

P - Press

FNPT - Female NPT Threads

MNPT - Male NPT Threads

FTG - Plain end fitting

F - Flange

ProPress 304 stainless rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with listed Viega Eco-pipe and 304 stainless steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Model	Type	Size (in.)	Rated Pressure (psig)
6011	Adapter (P x MNPT)	1/2 x 1/2, 3/4; 3/4 x 1/2, 3/4, 1; 1 x 3/4, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/2; 2 x 2	175
6012	Adapter (P x FNPT)	1/2 x 1/2; 3/4 x 1/2, 3/4; 1 x 1/a2, 3/4, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/4, 1-1/2; 2 x 1, 1-1/2, 2	175
6056	Cap	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175

6015	Coupling (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175
6015.5	Slip coupling (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175
6059	Flange adapter (P x F)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175
6016	90 Degree elbow (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175
6016.1	90 Degree elbow (FTG x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175
6026	45 Degree elbow (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175
6026.1	45 Degree elbow (FTG x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175
6018	Tee (P x P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175
6018	Reducing tee (P x P x P)	3/4 x 3/4 x 1/2; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1-1/2 x 1/2, 3/4, 1; 2 x 2 x 1/2, 3/4, 1, 1-1/2	175
6017.2	Reducing tee (P x P x FNPT)	3/4 x 3/4 x 1/2, 3/4; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1-1/2 x 1/2, 3/4, 1; 2 x 2 x 1/2, 3/4, 1	175
6015.1	Reducer (FTG x P)	3/4 x 1/2; 1 x 1/2, 3/4; 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1/2, 3/4, 1; 2 x 1/2, 3/4, 1; 1-1/2	175
6060	Union (P x P)	1/2, 3/4, 1, 1-1/4; 1-1/2, 2	175

ProPress 316 rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with Viega Eco pipe and Viega 316 stainless steel sprinkler pipe and are to be installed in accordance with the manufacturer's installation instructions.

Model	Type	Size (in.)	Rated Pressure (psig)
4011	Adapter (P x MNPT)	1/2 x 1/2, 3/4; 3/4 x 1/2, 3/4, 1; 1 x 3/4, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/2; 2 x 2	175

4012	Adapter (P x FNPT)	1/2 x 1/2; 3/4 x 1/2, 3/4; 1 x 1/2, 3/4, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/4, 1-1/2; 2 x 1, 1-1/2, 2	175
4056	Cap	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4015	Coupling (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4015.5	Slip Coupling (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4059	Flange Adapter (P x F)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4016	90 Degree Elbow (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4016.1	90 Degree Elbow (FTG x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4026	45 Degree Elbow (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4026.1	45 Degree Elbow (FTG x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4018	Tee (P x P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175
4018	Reducing Tee (P x P x P)	3/4 x 3/4 x 1/2; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1-1/2 x 1/2, 3/4, 1; 2 x 2 x 1/2, 3/4, 1, 1-1/2	175
4017.2	Reducing Tee (P x P x FNPT)	3/4 x 3/4 x 1/2, 3/4; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1-1/2 x 1/2, 3/4, 1; 2 x 2 x 1/2, 3/4, 1	175
4015.1	Reducer (FTG x P)	3/4 x 1/2; 1 x 1/2, 3/4; 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1/2, 3/4, 1; 2 x 1/2, 3/4, 1, 1-1/2	175
4060	Union (P x P)	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	175

P - Press

F - Flange

FNPT - Female NPT Threads

MNPT - Male NPT Threads

FTG - Pipe End Fitting

**Press fitting**

Model ProPress rubber gasketed fittings constructed from Red Brass in the following types, sizes and rated pressures are intended for use with copper tube, Type K, L and M and are to be installed in accordance with the manufacturer's installation instructions.

Model	Type	Size (in.)	Rated Pressure (psig)
2956	Cap	3/4, 1, 1-1/4, 1-1/2, 2	175
0956	Cap	2-1/2, 3, 4	175
2915	Coupling (P x P)	3/4, 1, 1-1/4, 1-1/2, 2	175
0915	Coupling (P x P)	2-1/2, 3, 4	175
2915.2	Reducing coupling (P x P)	3/4 x 1/2; 1 x 1/2, 3/4; 1-1/4 x 3/4, 1; 1-1/2 x 3/4, 1, 1-1/4; 2 x 3/4, 1, 1-1/4, 1-1/2	175
2916	90° Elbow (P x P)	3/4, 1, 1-1/4, 1-1/2, 2	175
0916	90° Elbow (P x P)	2-1/2, 3, 4	175
2916.1	90° Elbow (FTG x P)	3/4, 1, 1-1/4, 1-1/2, 2	175
0916.1	90° Elbow (FTG x P)	2-1/2, 3, 4	175
2926	45° Elbow (P x P)	3/4, 1, 1-1/4, 1-1/2, 2	175
0926	45° Elbow (P x P)	2-1/2, 3, 4	175
2926.1	45° Elbow (FTG x P)	3/4, 1, 1-1/4, 1-1/2, 2	175
0926.1	45° Elbow (FTG x P)	2-1/2, 3, 4	175
2915.1	Reducer (FTG x P)	1-1/4 x 1; 1-1/2 x 1, 1-1/4; 2 x 1, 1-1/4, 1-1/2	175
0915.1	Reducer (FTG x P)	2-1/2 x 2; 3 x 2, 2-1/2; 4 x 2, 2-1/2, 3	175
2918	Tee (P x P x P)	3/4, 1, 1-1/4, 1-1/2, 2	175
0918	Tee (P x P x P)	2-1/2, 3, 4	175



2918	Reducing tee (P x P x P)	1/2 x 1/2 x 1; 1 x 1/2, 3/4 x 1; 1 x 1 x 1/2, 3/4, 1-1/4; 1-1/4 x 1/2 x 1-1/4; 1-1/4 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4, 1; 1-1/2 x 1/2 x 1-1/2; 1-1/2 x 1 x 1, 1-1/2; 1-1/2 x 1-1/4 x 1, 1-1/4; 1-1/2 x 1-1/2 x 1/2, 3/4, 1, 1-1/4; 2 x 1/2 x 2; 2 x 1 x 1, 2; 2 x 1-1/4 x 1-1/4; 2 x 1-1/2 x 1, 1-1/4, 1-1/2, 2; 2 x 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2	175
0918	Reducing tee (P x P x P)	2-1/2 x 1-1/2 x 1/2, 3/4; 2-1/2 x 2 x 2-1/2; 3 x 2, 2-1/2 x 3; 3 x 3 x 1-1/2, 2, 2-1/2; 4 x 4 x 1-1/2, 2, 2-1/2, 3; 4 x 2, 2-1/2 x 4	175
0917.2	Reducing tee NPT	2-1/2 x 3/4, 2 x 2-1/2; 3 x 3/4, 2 x 3; 3 x 3 x 3/4; 4 x 3/4 x 4; 4 x 2 x 4; 4 x 4 x 3/4, 2	175
0911	Adapter NPT (P x MNPT)	2-1/2 x 2-1/2; 3 x 3; 4 x 4	175
0912	Adapter NPT (P x FNPT)	2-1/2, 3, 4	175

**Press fitting**

Zero Lead ProPress rubber gasketed fittings in the following types, sizes and rated pressures are intended for use with copper tube, Type K, L and M and are to be installed in accordance with the manufacturer's installation instructions.

Model	Type	Size (in.)	Rated Pressure (psig)
2925.5ZL	90° Elbow drop w/wall plate, P x F NPT	3/4 x 3/4	175
2917.2ZL	Tee P x P x F NPT	3/4 x 3/4 x 1/2, 3/4; 1 x 1 x 1/2, 3/4; 1-1/4 x 1-1/4 x 1/2, 3/4; 1-1/2 x 1-1/2 x 1/2, 3/4; 2 x 2 x 1/2, 3/4	175
2911ZL	Male adapter P x M NPT	3/4 x 1/2, 3/4, 1; 1 x 3/4, 1, 1-1/4; 1-1/4 x 1, 1-1/4; 1-1/2 x 1-1/4, 1-1/2, 2; 2 x 1-1/2, 2	175

2912ZL	Female adapter P x F NPT	3/4 x 1/2, 3/4; 1 x 1/2, 3/4, 1, 1-1/4; 1-1/4 x 1/2, 1, 1-1/4, 1-1/2; 1-1/2 x 1-1/4, 1-1/2; 2 x 2	175
2967ZL	Di-electric union, P x F NPT	3/4, 1, 1-1/4, 1-1/2, 2	175
2914.2ZL	90° Elbow P x FNPT	3/4 x 1/2, 3/4; 1 x 1/2, 1; 1-1/4 x 1-1/4; 1-1/2 x 1-1/2; 2 x 2	175
2960ZL	Union P x P	3/4, 1, 1-1/4, 1-1/2, 2	175
2962ZL	Union P x FNPT	3/4, 1, 1-1/4, 1-1/2, 2	175
2965ZL	Union P x MNPT	3/4, 1, 1-1/4, 1-1/2, 2	175
2959.5ZL	Adapter flange P x Flange	1, 1-1/4, 1-1/2, 2	175
2915.1ZL	Reducer FTG x P	1-1/2 x 1/2; 2 x 1/2, 3/4	175

All model ProPress rubber gasketed fittings are suitable for use in dry pipe systems for temperatures to -40 degree F.

P - Press

F NPT - Female National Pipe Thread

M NPT - Male National Pipe Thread

FTG - Copper tube end (fitting)

Last Updated on 2020-02-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"