

## Tech Data

# Viega Pressgun 6 and the Pressgun Picco 6



### Description

The Pressgun 6 and Pressgun Picco 6 deliver consistent, secure connections in 6 to 8 seconds depending on the tool. The Pressgun 6 can press ½" to 2" PureFlow®, ½" to 4" ProPress® and ½" to 2" MegaPress®. The Pressgun Picco 6 lets you press ½" to 1" PureFlow, ½" to 1" ProPress and ½" or ¾" MegaPress.

### Features

- Swivel attachment mounting/retaining pin
- Simple LED display
- Cylinder head and jaw intake made of steel
- 270° rotating cylinder head
- Latest battery cell technology
- Forward and backward compatibility with RIDGID® and Viega batteries

### Operating Parameters

- Temperature Range: 14°F to 122°F
- Shearing Force at Piston: 7200 lbf. (32 kN) for Pressgun 6; 5400 lbf. (24 kN) for Picco 6
- Nominal Output: 324 W

### Approved Applications

- See our approved applications chart for all listings and link that to the page [here](#).



Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. **Installation by non-professionals may void Viega LLC's warranty.**



This document is subject to updates. For the most current Viega technical literature please visit [www.viega.us](http://www.viega.us).

	VIEGA PRESSGUN PICCO 6		VIEGA PRESSGUN 6		
	Jaws	C1 Actuator & Rings	Jaws	V1 Actuator & Rings	V2 Actuator & Rings
ProPress®	½", ¾", 1" and 1¼"	½" - 1¼"	½", ¾", 1", 1¼", 1½" and 2"	½" - 1¼"	½" - 4"
MegaPress®	½" - ¾"		½", ¾" and 1"		1¼" - 2"
PureFlow®	⅜", ½", ⅝", ¾", 1", 1¼" and 1½"		½", ⅝", ¾", 1", 1¼", 1½" and 2"		
	Jaws	P1 Actuator & Rings	Jaws	Z1 Actuator & Rings	Z2 Actuator & Rings
SeaPress®	12-35 mm	12-35 mm	12-54 mm	12-35 mm	42-108 mm

**> Viega LLC**  
585 Interlocken Blvd.  
Broomfield, CO 80021

Phone (800) 976-9819  
[www.viega.us](http://www.viega.us)

TD-XX MMY Product Name

