

Connected in quality.

ORIGINAL EQUIPMENT MANUFACTURER SOLUTIONS

— REDUCE PRODUCT FABRICATION TIME WITH VIEGA® PRESS TECHNOLOGY



Many Viega products can be pressed in just seconds, a significant time savings over traditional joining methods. There's no wait time for curing or drying, so pressure tests can be performed immediately.



With no hot work, fire watches are unnecessary. That means there's no need for additional manpower, plus you can skip the messy or labor-intensive tools.



Viega is a trusted leader in press technology, so build with confidence. With a heritage of engineering press fittings for a variety of materials and strict quality control, you'll know you're getting the very best when you choose Viega.



Viega press fittings offer safer and more consistent connections than traditional methods. Unlike grooved and threaded connections, you don't have to jeopardize the integrity of the pipe to get a dependable connection.

viega

PROPRESS®

COPPER PRESS FITTINGS

SEALING ELEMENTS: EPDM

OPERATING TEMPERATURE: 0°F TO 250°F

PRESSURE: 300PSI

SIZE: ½" – 4"

Viega ProPress is the proven solution for nearly any industrial, commercial or residential project. With choices in sealing elements, system-matched tools, rings and jaws, press connections are made in seconds, making Viega ProPress suitable for many standard applications.



PROPRESS® 316

316 STAINLESS STEEL PRESS FITTINGS

SEALING ELEMENTS: EPDM

OPERATING TEMPERATURE: 0°F TO 250°F

PRESSURE: 200PSI

SIZE: ½" – 4"

Designed for Copper Tube Size (CTS), Viega ProPress 316 stainless steel is engineered for harsh industrial environments where the piping systems may come into contact with corrosive cleaning liquids. Viega ProPress 316 stainless steel is a great option for water, air, acidic, and cleaning solution applications while being light and easy to work with.



PUREFLOW®

PEX PRESS FITTINGS

MECHANICAL PRESS CONNECTION

OPERATING TEMPERATURE: 180°F (POTABLE); 200°F (HYDRONIC)

PRESSURE: UP TO 160PSI

SIZE: ¾" – 2"

PureFlow is the only system in the industry that offers press-to-press transition fittings – allowing you to easily transition from PureFlow PEX to ProPress in traditional branch and tee installations. Looking to reduce the number of fittings behind the wall? PureFlow lets you install remote manifolds giving each fixture in a building its own PEX tubing line.



MEGAPRESS®

CARBON STEEL PRESS FITTINGS

SEALING ELEMENTS: EPDM

OPERATING TEMPERATURE: 0°F TO 250°F

PRESSURE: 200PSI

SCH: 5 - 40

SIZE: ½" - 4"

Ideal for facility utility needs, the Viega MegaPress system is easy to use, flameless, and reliable. Most often used for fire sprinklers, hydronics, and compressed air, MegaPress leaves no joining material buildup, exposed threads or tarnish, creating a clean, professional appearance.



MEGAPRESS® G

CARBON STEEL PRESS FITTINGS

SEALING ELEMENTS: HNBR

OPERATING TEMPERATURE: -40°F TO 180°F

PRESSURE: 125PSI

SCH: 5 - 40

SIZE: ½" - 4"

Viega MegaPressG fittings are a safe and fast way to connect gas pipe. MegaPressG press fittings and valves are easy to install, saving you time and labor, and are compatible with a wide range of approved applications, including natural gas and propane.



MEGAPRESS® 304 + 316

STAINLESS STEEL PRESS FITTINGS

SEALING ELEMENTS: FKM*, EPDM

OPERATING TEMPERATURE: 0°F TO 284°F

PRESSURE: 200PSI

SCH: 5 - 40

SIZE: ½" - 4"

Designed for Iron Pipe Size (IPS) stainless steel, Viega MegaPress 304 and 316 stainless steel press fittings support more applications than ever before. From potable water to acid and cleaning agents, Viega MegaPress stainless stands up to the toughest jobs while keeping its appearance clean.

* FKM Sealing element available. Operating Temperature for MegaPress : 14°F to 284°F



POTABLE WATER

HYDROGEN,
OXYGEN,
NITROGEN, CO,
CO2

STEAM
(5PSI EPDM,
15PSI FKM)

COMPRESSED
AIR

PROPRESS

RAINWATER

CHILLED WATER

ETHANOL

LUBE OIL

DIESEL FUEL

RAINWATER
MINERAL OIL

LUBE OIL

PROPANE

NATURAL GAS

MEGAPRESS

COMPRESSED
AIR


NITROGEN

CARBON
DIOXIDE

ARGON

HYDROGEN

THOUSANDS OF POSSIBLE OEM APPROVED APPLICATIONS



VISIT VIEGA.US TO SEE A COMPLETE APPLICATIONS CHART

VIEGA® PRESS TECHNOLOGY

No other manufacturer can offer the same press technology across multiple piping systems.

This document is subject to updates. For the most current Viega literature please visit www.viega.us. The term Viega does not apply to a specific company within the various separate and distinct companies comprising the Viega group of companies. The term Viega as used in this publication refers to the Viega brand itself or generally to the Viega group of companies. References to activities in North America specifically refer to activities of Viega LLC. Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. Installation by non-professionals may void Viega LLC's warranty. ©2023, Viega®, MegaPress®, ProPress®, Smart Connect®, XL®, and Viega: Connected in quality® are trademarks of Viega Holding GmbH & Co. KG.

01904_EN_1022

Viega LLC

585 Interlocken Blvd.
Broomfield, CO 80021
USA

Phone (800) 976-9819

viega.us



SCAN
WITH PHONE
TO LEARN MORE

viega