**Connected in quality.** 

iega

# **GOVERNMENT** PIPE SYSTEM SOLUTIONS

#### NO FLAME CONNECTIONS with viega® press technology



Many Viega products can be pressed in seconds, a significant time savings over traditional joining methods. There's no wait time for curing or drying, so pressure tests can be performed immediately.



With no welding or soldering flames, fire watches are unnecessary. That means there's no need for additional manpower, plus you can skip the messy or labor-intensive tools.



Viega is a trusted leader in press technology, so build with confidence. With a heritage of engineering press fittings for a variety of materials and strict quality control, you'll know you're getting the very best when you choose Viega.

Viega press fittings are simpler and safer to install than traditional methods. Installations can be made anywhere, in any condition. Unlike grooved and threaded connections, you don't have to jeopardize the integrity of the pipe to get the dependable connection you need.



#### **PROPRESS**<sup>®</sup> COPPER PRESS FITTINGS

SEALING ELEMENTS: EPDM OPERATING TEMPERATURE: 0°F TO 250°F PRESSURE: 300PSI SIZE: ½" – 4"

Viega ProPress is the proven solution for nearly any industrial, commercial or residential project. With choices in sealing elements, system-matched tools, rings and jaws, press connections are made in seconds, making Viega ProPress suitable for many standard applications.



#### **PROPRESS<sup>®</sup> 316** 316 STAINLESS STEEL PRESS FITTINGS

SEALING ELEMENTS: EPDM OPERATING TEMPERATURE: 0°F TO 250°F PRESSURE: 200PSI SIZE: ½" – 4"

Designed for Copper Tube Size (CTS), Viega ProPress 316 stainless steel is engineered for harsh industrial environments where the piping systems may come into contact with corrosive cleaning liquids. Viega ProPress 316 stainless steel is a great option for water, air, acidic, and cleaning solution applications while being light and easy to work with.



#### **PUREFLOW<sup>®</sup>** PEX PRESS FITTINGS

MECHANICAL PRESS CONNECTION OPERATING TEMPERATURE: 180°F (POTABLE); 200°F (HYDRONIC) PRESSURE: UP TO 160PSI SIZE: %" – 2"

PureFlow is the only system in the industry that offers press-to-press transition fittings – allowing you to easily transition from PureFlow PEX to ProPress in traditional branch and tee installations. Looking to reduce the number of fittings behind the wall? PureFlow lets you install remote manifolds giving each fixture in a building its own PEX tubing line.



#### MEGAPRESS<sup>®</sup> CARBON STEEL PRESS FITTINGS

SEALING ELEMENTS: EPDM OPERATING TEMPERATURE: 0°F TO 250°F PRESSURE: 200PSI SCH: 5 - 40 SIZE: ½" – 2"

Ideal for facility utility needs, the Viega MegaPress system is easy to use, flameless, and reliable. Most often used for fire sprinklers, hydronics, and compressed air, MegaPress leaves no joining material buildup, exposed threads or tarnish, creating a clean, professional appearance.



### MEGAPRESS<sup>®</sup> G CARBON STEEL PRESS FITTINGS

SEALING ELEMENTS: HNBR OPERATING TEMPERATURE: -40°F TO 180°F PRESSURE: 125PSI SCH: 5 - 40 SIZE: ½" – 4"

Viega MegaPressG fittings are a safe and fast way to connect gas pipe. MegaPressG press fittings and valves are easy to install, saving you time and labor, and are compatible with a wide range of approved applications, including natural gas and propane.



# **MEGAPRESS<sup>®</sup>** CuNi

#### **COPPER-NICKEL PRESS FITTINGS**

SEALING ELEMENTS: FKM OPERATING TEMPERATURE: 23°F TO 284°F PRESSURE: 200PSI SIZE: ½" – 4"

Now with NAVSEA approval, Viega MegaPress CuNi system is a 90:10 copper-nickel alloy that is specifically designed for marine and industrial pipe joining applications to stand up to the harsh environments of the sea. The MegaPress CuNi system is approved for a variety of applications and provides an economical and reliable installation of Class 200 and Schedule 40 copper-nickel pipe.





#### INDUSTRY CODES /STANDARDS / LISTINGS

\*For additional government/military codes, standards and approvals, go to: www.viega.us/gov

- ABS
- ANSI / LC4
- ATSM B16.51
- FM Class 1920
- HUD

- IAPMO PS117
   IPC / IMC IFGC
- NFPA 54
   NFPA 58
- ICC-ES AC156
- NSF 61G
  PHCC NFPC
- UL 213
   UPC / UMC

## **1000+ INDUSTRIAL AND MARINE** APPROVED APPLICATIONS



#### VISIT VIEGA.US TO SEE A COMPLETE APPLICATIONS CHART

**VIEGA® PRESS TECHNOLOGY** 

No other manufacturer can offer the same press technology across multiple piping systems.

This document is subject to updates. For the most current Viega literature please visit www.viega.us The term Viega does not apply to a specific company within the various separate and distinct companies comprising the Viega group of companies. The term Viega as used in this publication refers to the Viega brand itself or generally to the Viega group of companies. References to activities in North America specifically refer to activities of Viega LLC. Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. Installation by non-professionals may void Viega LLC's warranty. ©2023, Viega®, MegaPress®, ProPress®, Smart Connect®, XL®, and Viega: Connected in quality® are trademarks of Viega Holding GmbH & Co. KG.

01910\_EN\_1022

Viega LLC 585 Interlocken Blvd. Broomfield, CO 80021 USA

Phone (800) 976-9819

viega.us



SCAN WITH PHONE TO LEARN MORE

