Tech Data

Viega MegaPress® 316 Check Valve **Model 5174**



Description

Viega's MegaPress 316 Check Valve is a spring check valve with a 316 stainless-steel body, stainless-steel

spring, and MegaPress press ends. It is approved for potable water applications.

Features

- EPDM sealing element
- 0.5 psi cracking pressure
- Low pressure loss
- Silent operation
- Smart Connect® technology

Operating Parameters

■ Temperature Range: 0°F to 250°F


■ Max Operating Pressure: 250 psi

Listings and Certifications

- Conforms to MSS SP-80
- NSF_® 61-372, C.HOT

Approved Applications

- Hot and Cold Water
- Chilled Water
- Hydronic Heating Water



Flow is in one direction




This document is subject to updates. For the most current Viega technical literature, please visit www.viega.us.

Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. Installation by non-professionals may void Viega LLC's warranty.




Zero Lead identifies Viega products meeting the lead free requirements of NSF/ANSI/CAN 61 through testing under NSF/ANSI/CAN 372 (0.25% or less maximum weighted average lead content).

Pressure Drop



Viega MegaPress 316 Check Valve - Model 5174



Part No. 316 EPDM	Size (in) 1	A (in)	L (in)
29050	1/2	2.244	4.488
29055	3/4	2.323	4.685
29060	1	2.717	5.472
29065	11⁄4	2.992	6.732
29070	1½	3.346	7.165
29075	2	3.937	7.953



Phone (800) 976-9819 www.viega.us

