Tech Data

Viega ProPress® 316 Ball Valve Model 4070



Description

The ProPress 316 twopiece ball valve can be used in a variety of commercial and industrial applications. The EPDM sealing elements make it the

perfect choice for potable water systems while the durable 316 stainless steel allows it to stand up to some of the harshest environments found in power plants, refineries, utilities, and mills. The double EPDM stem seals prevent leaks without the need for constant adjustment. The 316 stainless steel ball valves are available in sizes ranging from ½" to 2" and are equipped with Viega's unique Smart Connect® technology for easy identification of unpressed connections during pressure testing.

Features

- ProPress press ends
- 316 stainless steel ball and stem
- Full port, two piece design
- Blowout-proof stainless steel stem
- Reinforced PTFE seats
- Lockable metal handle

Ratings

- 250 CWP
- Temperature Range: 0°F to 250°F
 Max. Operating Pressure: 200 psi



This document is subject to updates. For the most current Viega technical literature please visit www.viega.us.


Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. Installation by non-professionals may void Viega LLC's warranty.

Approvals

- Conforms to MSS SP-110
- NSF_®-61-372

Component	Material			
Body	316 Stainless Steel			
Ball	316 Stainless Steel			
Seat	Reinforced PTFE			
Stem	316 Stainless Steel			
Stem Seals	EPDM			
Nut	Zinc-plated Steel			
Handle	Zinc-plated Steel			
Handle Cover	Polyvinyl			
Sealing Element	EPDM			

Viega ProPress 316 Ball Valve - Model 4070



Part No.	Size (in)	A (in)	A1 (in)	L (in)	L1 (in)	L2 (in)	H (in)
81080	1/2	0.89	1.17	1.64	1.92	5.55	2.44
81085	3/4	1.06	1.36	1.97	2.26	5.55	2.52
81090	1	1.18	1.57	2.09	2.48	5.55	2.68
81095	11/4	1.45	1.72	2.48	2.75	6.10	3.09
81100	1½	1.83	1.81	3.26	3.24	6.10	3.34
81105	2	1.97	2.18	3.54	3.78	6.10	3.66



Phone (800) 976-9819 www.viega.us

