

# CERTIFICATE OF COMPLIANCE

**Certificate Number** EX6157  
**Report Reference** EX6157-2002-10-21  
**Date** 2021-October-01

**Issued to:** VIEGA L L C  
585 Interlocken Blvd  
Broomfield CO, 80021 US

**This is to certify that representative samples of** FITTINGS, RUBBER GASKETED  
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


**Standard(s) for Safety:** UL 213-Standard for Safety for Rubber Gasketed Fittings for Fire Protection Service

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE


**Certificate Number** EX6157  
**Report Reference** EX6157-2002-10-21  
**Date** 2021-October-01

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

**Models:**  
 Rubber Gasketed Fittings

Model ProPress rubber gasketed fittings constructed from copper in the following types, sizes, and rated pressures are intended for use with copper tube, Type K, L and M and are to be installed with a Viega approved Electro-Hydraulic Press Tool in accordance with the manufacturer's installation instructions:

| Model    | Type                          | Size (in.)   | Rated Pressure<br>psig (kPa) |
|----------|-------------------------------|--|------------------------------|
| 2956     | Cap                           | 3/4, 1, 1-1/4, 1-1/2, 2  | 175 (1210)                   |
| 0956XL   | Cap                           | 2-1/2, 3, 4  | 175 (1210)                   |
| 2915     | Coupling with stop (P x P)    | 3/4, 1, 1-1/4, 1-1/2, 2  | 175 (1210)                   |
| 0915XL   | Coupling with stop (P x P)    | 2-1/2, 3, 4  | 175 (1210)                   |
| 2915.2   | Reducing coupling (P x P)     | 3/4 x 1/2;<br>1 x 1/2, 1 x 3/4;<br>1-1/4 x 3/4, 1-1/4 x 1;<br>1-1/2 x 3/4, 1-1/2 x 1, 1-1/2 x 1-1/4;<br>2 x 3/4, 2 x 1, 2 x 1-1/4, 2 x 1-1/2 | 175 (1210)                   |
| 0915.5XL | Coupling without stop (P x P) | 4  | 175 (1210)                   |
| 2915.3   | Repair Coupling (P x P)       | 3/4, 1, 1-1/4, 1-1/2, 2  | 175 (1210)                   |
| 2916     | 90° Elbow (P x P)             | 3/4, 1, 1-1/4, 1-1/2, 2  | 175 (1210)                   |
| 0916XL   | 90° Elbow (P x P)             | 2-1/2, 3, 4  | 175 (1210)                   |
| 2916.1   | 90° Elbow (FTG x P)           | 3/4, 1, 1-1/4, 1-1/2, 2  | 175 (1210)                   |
| 0916.1XL | 90° Elbow (FTG x P)           | 2-1/2, 3, 4  | 175 (1210)                   |



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number**    EX6157  
**Report Reference**     EX6157-2002-10-21  
**Date**                      2021-October-01

|          |                                 |   |                              |
|----------|---------------------------------|---|------------------------------|
| 2926     | 45° Elbow (P x P)               | 3/4, 1, 1-1/4, 1-1/2, 2   | 175 (1210)                   |
| 0926XL   | 45° Elbow (P x P)               | 2-1/2, 3, 4   | 175 (1210)                   |
| 2926.1   | 45° Elbow (FTG x P)             | 3/4, 1, 1-1/4, 1-1/2, 2   | 175 (1210)                   |
| 0926.1XL | 45° Elbow (FTG x P)             | 2-1/2, 3, 4   | 175 (1210)                   |
| 2915.1   | Reducer (FTG x P)               | 1-1/4 x 1;<br>1-1/2 x 1, 1-1/2 x 1-1/4;<br>2 x 1, 2 x 1-1/4, 2 x 1-1/2  | 175 (1210)                   |
| 0915.1XL | Reducer (FTG x P)               | 2-1/2 x 2;<br>3 x 2, 3 x 2-1/2;<br>4 x 2, 4 x 2-1/2, 4 x 3  | 175 (1210)                   |
| 2918     | Tee (P x P x P)                 | 3/4, 1, 1-1/4, 1-1/2, 2   | 175 (1210)                   |
| 0918XL   | Tee (P x P x P)                 | 2-1/2, 3, 4   | 175 (1210)                   |
| Model    | Type                            | Size (in.)  | Rated Pressure<br>psig (kPa) |
| 2918     | Reducing tee<br><br>(P x P x P) | 1/2 x 1/2 x 1;<br>3/4 x 3/4 x 1;<br>1 x 1 x 1/2, 1 x 1 x 3/4, 1 x 1 x 1-1/4;<br>1-1/4 x 1 x 1/2, 1-1/4 x 1 x 3/4;<br>1-1/4 x 1-1/4 x 1/2, 1-1/4 x 1-1/4 x 3/4, 1-1/4 x 1-1/4 x 1;<br>1-1/2 x 1 x 1, 1-1/2 x 1 x 1-1/2;<br>1-1/2 x 1-1/4 x 1, 1-1/2 x 1-1/4 x 1-1/4;<br>1-1/2 x 1-1/2 x 1/2, 1-1/2 x 1-1/2 x 3/4, 1-1/2 x 1-1/2 x 1, 1-1/2 x<br>1-1/2 x 1-1/4;<br><br>2 x 1-1/4 x 1-1/4;<br>2 x 1-1/2 x 1, 2 x 1-1/2 x 1-1/4, 2 x 1-1/2 x 1-1/2, 2 x 1-1/2 x 2;<br>2 x 2 x 1/2, 2 x 2 x 3/4, 2 x 2 x 1, 2 x 2 x 1-1/4, 2 x 2 x 1-1/2 | 175 (1210)                   |
| 0918XL   | Reducing tee<br><br>(P x P x P) | 2-1/2 x 2-1/2 x 1/2, 2-1/2 x 2-1/2 x 3/4;<br>2-1/2 x 2 x 2-1/2;<br>3 x 2 x 3;   | 175 (1210)                   |



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




# CERTIFICATE OF COMPLIANCE

**Certificate Number** EX6157  
**Report Reference** EX6157-2002-10-21  
**Date** 2021-October-01

|           |                             |   |            |
|-----------|-----------------------------|---|------------|
|           |                             | 3 x 2-1/2 x 3<br>3 x 3 x 1-1/2, 3 x 3 x 2, 3 x 3 x 2-1/2;<br>4 x 4 x 1-1/2, 4 x 4 x 2, 4 x 4 x 2-1/2, 4 x 4 x 3 |            |
| *0917.2XL | Reducing tee NPT            | 2-1/2 x 3/4, 2-1/2 x 2;<br>3 x 3/4, 3 x 2;<br>4 x 3/4;<br>4 x 2   | 175 (1210) |
| 0911XL    | Adapter NPT<br>(P x MNPT)   | 2-1/2 x 2-1/2;<br>3 x 3;<br>4 x 4   | 175 (1210) |
| 0912XL    | Adapter NPT<br>(P x FNPT)   | 2-1/2, 3, 4   | 175 (1210) |
| 0959.5XL  | Flange Adapter (P x Flange) | 2-1/2, 3, 4   | 175 (1210) |

All model ProPress rubber gasketed fittings are suitable for use in dry pipe systems for temperatures to -40 degree F.

P - Press  
 F NPT - Female National Pipe Thread  
 M NPT - Male National Pipe Thread  
 FTG – Copper tube end (fitting)



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

